

AD-A158 776

FAR-FIELD BOUNDARY CONDITIONS IN NUMERICAL SOLUTIONS OF
THE NAVIER-STOKES EQUATIONS(U) FLORIDA UNIV GAINESVILLE
P J MCKENNA 10 MAY 85 AFOSR-TR-85-0625 AFOSR-83-0330


1/1

UNCLASSIFIED

F/G 20/4

NL

							END						
							FILED						
							DTIC						



NATIONAL BUREAU OF STANDARDS
MICROCOPY RESOLUTION TEST CHART

AFOSR-TR- 85 - 0625

2

Far-Field Boundary Conditions in Numerical
Solutions of the Navier-Stokes Equations

AD-A158 776

P.J. McKenna

DTIC FILE COPY

Final Report AFOSR Grant 83-0330

DTIC
ELECTE
AUG 29 1985
S D G

Approved for release;
distribution unlimited.

85 8 21 013

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE

REPORT DOCUMENTATION PAGE

1a. REPORT SECURITY CLASSIFICATION Unclassified AD-A158 776			1b. RESTRICTIVE MARKINGS		
2a. SECURITY CLASSIFICATION AUTHORITY ---			3. DISTRIBUTION/AVAILABILITY OF REPORT Approved for public release; distribution unlimited		
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE N/A			5. MONITORING ORGANIZATION REPORT NUMBER(S) AFOSR-TR- 85 - 0625		
4. PERFORMING ORGANIZATION REPORT NUMBER(S)			7a. NAME OF MONITORING ORGANIZATION AFOSR		
6a. NAME OF PERFORMING ORGANIZATION University of Florida		6b. OFFICE SYMBOL (If applicable)	7b. ADDRESS (City, State and ZIP Code) Bldg. 410 Bolling AFB, D.C. 20332-6448		
6c. ADDRESS (City, State and ZIP Code) Gainesville, FL 32611		9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER AFOSR-83-0330			
8a. NAME OF FUNDING/SPONSORING ORGANIZATION AFOSR		8b. OFFICE SYMBOL (If applicable) NM	10. SOURCE OF FUNDING NOS.		
8c. ADDRESS (City, State and ZIP Code) Bldg. 410 Bolling AFB, D.C. 20332-6448		PROGRAM ELEMENT NO. 61102F	PROJECT NO. 2304	TASK NO. A3	WORK UNIT NO.
11. TITLE (Include Security Classification) Far Field Boundary Conditions in Numerical Solutions of the Navier-Stokes Equations					
12. PERSONAL AUTHOR(S) P. J. McKenna					
13a. TYPE OF REPORT Final		13b. TIME COVERED FROM 24 Oct 84 to 1 Apr 85	14. DATE OF REPORT (Yr., Mo., Day) 10 May 1985		15. PAGE COUNT 59
16. SUPPLEMENTARY NOTATION					
17. COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)		
FIELD	GROUP	SUB. GR.	artificail boundary conditions, Navier-Stokes equations		
XX	XXXXXXXXXX	XX			
19. ABSTRACT (Continue on reverse if necessary and identify by block number)					
<p>The purpose of this project was to investigate the artificial boundary conditions which must be imposed at the boundary of a numerical grid. Numerical experiments were performed which evaluated various boundary conditions of this type. Of particular interest was the question of whether linearization around the flow at infinity provides an adequate choice of boundary condition for the fully nonlinear equations. Inflow-outflow conditions as well as several choices of periodic boundary conditions were considered. The inflow-outflow conditions worked reasonably well for two dimensional problems. For the periodic conditions, results were mixed. Concerns about over specification when using pure periodic conditions proved to be groundless. However, the method failed when attempting to use periodicity in the two sideways traveling periodic waves.</p> <p><i>John P. Thomas, Capt., USAF</i></p>					
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT UNCLASSIFIED/UNLIMITED <input checked="" type="checkbox"/> SAME AS RPT. <input checked="" type="checkbox"/> DTIC USERS <input type="checkbox"/>			21. ABSTRACT SECURITY CLASSIFICATION Unclassified		
22a. NAME OF RESPONSIBLE INDIVIDUAL John P. Thomas, Capt., USAF			22b. TELEPHONE NUMBER (Include Area Code) (202)767-5026	22c. OFFICE SYMBOL NM	

DD FORM 1473, 83 APR

EDITION OF 1 JAN 73 IS OBSOLETE.

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE

I INTRODUCTION

With the advent of high speed computers, new approaches to the solution of engineering problems have arisen. One such field is Computational Fluid Dynamics, in which numerical techniques such as finite differences are used to numerically integrate partial differential equations governing the physical phenomena. One problem with this approach is that on the boundary of the numerical grid, artificial boundary conditions must be imposed. Usually, these conditions are based on a linearization around the flow at infinity, and are thus non-physical. In this paper, we perform a series of numerical experiments, in which we evaluate various boundary conditions of this type, and investigate whether the linear model is an accurate representation of the fully non-linear equations.

The flow of fluid around obstacles in two dimensions is described by the compressible Navier-Stokes equations

$$(1) \quad \frac{\partial U}{\partial t} + \frac{\partial E}{\partial x} + \frac{\partial F}{\partial y} = 0$$

where

$$U = \begin{bmatrix} \rho \\ \rho u \\ \rho v \\ \rho e \end{bmatrix}$$

$$E = \begin{bmatrix} \rho u \\ \rho u^2 - \sigma_{xx} \\ \rho uv - \tau_{xy} \\ \rho ue - u\sigma_{xx} - v\tau_{xy} - \dot{q}_x \end{bmatrix}$$

$$F = \begin{bmatrix} \rho v \\ \rho uv - z_{xy} \\ \rho v^2 - \sigma_{yy} \\ \rho ve - \sigma_{yy} - uz_{yx} - \dot{q}_y \end{bmatrix}$$

$$\sigma_{xx} = -p - \left(\frac{2}{3}\right) \mu \vec{v} \cdot \vec{u} + 2\mu \frac{\partial u}{\partial x}$$

$$z_{xy} = \mu \left(\frac{\partial u}{\partial y} + \frac{\partial v}{\partial x} \right)$$

$$\sigma_{yy} = -p - \left(\frac{2}{3}\right) \mu \vec{v} \cdot \vec{u} + 2\mu \frac{\partial v}{\partial y}$$

$$\dot{q}_x = k \frac{\partial T}{\partial x} \quad \dot{q}_y = k \frac{\partial T}{\partial y}$$

$$p = \rho RT \quad \mu = \mu(T)$$

$$e = c_v T + (u^2 + v^2)/2.$$

Here, the four variables ρ, u, v, e represent the physical quantities of density, x- and y- components of velocity, and internal energy.

This nonlinear system of mixed parabolic-hyperbolic type in two space dimensions and time, with four independent variables must be solved in an exterior region in R^2 . The geometry will depend on the particular physical situation that one is attempting to model.

The situation we shall be interested in occurs in modelling

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A/1	



flight conditions, in which the conditions at infinity are prescribed with a large u -velocity and v -velocity zero and prescribed ρ_∞ and e_∞ . Fluid flows around an obstacle in x - y space.

Usually, this equation is solved numerically using a finite difference scheme of the Lax-Wendroff type, such as the MacCormack ADE method. Since these calculations can only be made on a finite grid of points in xy space, an artificial far-field boundary is created. This boundary ought be sufficiently far away from the object around which the fluid is flowing so that local phenomena are not neglected by omitting part of the region of fluid flow. On the other hand, the farther away the region is, the more grid-points need to be included and thus the more expensive and time-consuming the computations become.

One then has the problem of deciding what effect this new boundary has on the solution of the problem. Because of the viscosity terms in (1) and the additional artificial viscosity introduced by the finite difference schemes, some boundary conditions must be imposed.

As we shall show in this report on numerical experiments, considerable care must be exercised in the choice of the boundary conditions. If one is interested in steady state flow, then one starts off with an initial approximation, and hopes that the errors in the numerical solution propagate out of the region as transitory disturbances in the physical variables. One then expects to converge to the steady state flow.

We have previously shown that the incorrect choice of boundary conditions can give rise to some of the following phenomena: i) reflecting boundary conditions, in which the disturbances in the physical variables represented by the difference between the steady state flow and the initial conditions are not allowed to exit through the far-field boundary but instead continue echoing within the grid, and giving rise to spurious oscillatory solutions; ii) under-specified boundary conditions, in which large errors are introduced before convergence takes place.

In this paper, we first discuss the theory for simple linear hyperbolic systems in one and two space dimension. We then analyze several computational experiments in the light of this theory in two space dimensions.

II A REVIEW OF THE LINEAR CASE

The method used in the calculations which are the subject of this paper is the MacCormack alternating direction explicit

scheme. [6] [15]. This is a multistep efficient scheme which reduces in the linear case to the Lax-Wendroff scheme. For a diagonal $N \times N$ matrix A , this scheme approximates the equation $U_t + AU_x = 0$ by

$$(2) \quad \left[\begin{aligned} U_j^{n+1} &= U_j^n - A \frac{\Delta t}{\Delta x} (U_{j+1}^n - U_{j-1}^n) \\ &\quad + A^2 \left(\frac{\Delta t}{\Delta x} \right)^2 (U_{j+1}^n - 2U_j^n + U_{j-1}^n) \end{aligned} \right.$$

As usual, $\{j_1 < j < J\}$ represents the space step and n represents the time step. If we are considering the equation

$$U_t + AU_x = 0$$

on the region $\{(x,t), 0 < x < 1, t > 0\}$ then the analytic solution is determined by the initial conditions and boundary conditions at $x = 0$ and $x = 1$. If the first k eigenvalues are positive and the remaining $N - k$ are negative then the quantities $u_1 \dots u_k$ must be prescribed at $x = 0$ and $u_{k+1} \dots u_N$ must be prescribed at $x = 1$. Thus if $W_I = (u_1, u_2, \dots, u_k, 0, 0, \dots, 0)$ and $W_{II} = (0, 0, \dots, 0, u_{k+1}, \dots, u_N)$ then for well-posedness, the boundary conditions must be

$$W_I = f(t) + B_0 W_{II} \quad \text{at } x = 0$$

$$W_{II} = g(t) + B_1 W_I \quad \text{at } x = 1.$$

This gives a total of N boundary conditions. If either $k \times (n-k)$ matrix B_1 and the $(n-k) \times k$ matrix B_0 are non-zero, then the boundaries are reflecting, that is a wave in W_I travelling left to right will be reflected as a wave in W_{II} running right to left.

If a boundary is supposed to be non-physical, then it should not be reflecting, since the reflections would depend on the location of the artificial or numerical boundary.

Now let us consider the difference scheme of (2). If the grid points are given by $\{x_j\}_0^J$ with $x = 0$ and $x_J = 1$, then it is clear from (2) that $2N$ boundary conditions are required. Thus we must prescribe boundary conditions in such a way as to least affect the closeness of the numerical to the analytic solution.

This situation has been the subject of several papers. In [3], Gustaffson and Kreiss point out the danger of over-specification. By this is meant that all u_i are specified at both endpoints. This might be tempting because one might argue that if the boundary conditions $u_1 \dots u_k$ are given constants at $x = 0$, then eventually these same values will be assumed by these variables at $x = 1$. However, in [4] it is pointed out that convergence may or may not occur, depending on whether the number of grid points is odd or even.

A method which works well, as pointed out in [3], is to impose

$$\frac{\partial u_i}{\partial x}(1,t) = 0 \quad 1 < i < k.$$

$$\frac{\partial u_i}{\partial x}(0,t) = 0 \quad k+1 < i < n.$$

or in the numerical scheme

$$u_{i,J} = u_{i,J-1} \quad 1 < i < k.$$

$$u_{i,0} = u_{i,1} \quad k+1 < i < n.$$

This introduces small errors at the outflow but these errors do not propagate upstream. This is proved analytically by Parter [10].

In [12], many different numerical boundary conditions are given. The conclusion is that upwind differencing at the point of outflow

$$u_J^{n+1} = u_J^n + \lambda_i \left(\frac{\Delta t}{\Delta x} \right) (u_{J-1} - u_J)$$

is most accurate, although it converges with the same speed as the previously discussed $u_x = 0$.

The most serious error which one could make would be to prescribe conditions at the wrong end. In other words, since u_1 is right running, this would involve prescribing u_1 at $x = 1$ and imposing $u_{1x} = 1$ at $x = 0$. This would result in convergence to a

steady state which depends on the initial conditions.

III THE NAVIER-STOKES EQUATIONS AND CHARACTERISTIC VARIABLES:

We now begin our discussion of the equations of gas dynamics. We will neglect viscosity for the purposes of this analysis. We will assume that the flow is one-dimensional and subsonic and that the deviations from free-stream solutions are small. This will allow us to neglect second order terms.

There are many forms of this equation, but the one most suitable for the present discussion is

$$\frac{\partial U}{\partial t} + A \frac{\partial U}{\partial x} = 0$$

where

$$A = \begin{pmatrix} 0 & 1 & 0 \\ (\gamma-3)\frac{u^2}{2} & (3-\gamma)u & \gamma-1 \\ (\gamma-1)\frac{4^3}{\rho} - \frac{\gamma e u}{\rho} & \frac{\gamma e}{\rho} - \frac{3}{2}(\gamma-1)u^2 & \gamma u \end{pmatrix}$$

and

$$U = \begin{pmatrix} \rho \\ \rho u \\ e \end{pmatrix}$$

or in terms of physical variable

$$(3) \quad \frac{\partial \hat{U}}{\partial t} + \hat{A} \frac{\partial \hat{U}}{\partial x} = 0$$

where

$$\hat{A} = M^{-1} A M$$

and

$$M^{-1} = \begin{pmatrix} 1 & 0 & 0 \\ -u/p & 1/p & u \\ (\frac{\gamma-1}{2})u^2 & (1-\gamma)u & (\gamma-1) \end{pmatrix} \quad \hat{U} = \begin{bmatrix} \rho \\ u \\ p \end{bmatrix}$$

Here we make the key assumption that deviations from the free stream are going to be sufficiently small that we can treat the entries in the matrix A as being approximately constant (at least locally). Denote these frozen variables by 0-subscript. We then make the substitution

$$(4) \quad \begin{pmatrix} w_1 \\ w_2 \\ w_3 \end{pmatrix} = \begin{pmatrix} 1 & 0 & -1/c_0^2 \\ 0 & 1 & 1/\rho_0 c_0 \\ 0 & -1 & 1/\rho_0 c_0 \end{pmatrix} \begin{pmatrix} \rho \\ u \\ p \end{pmatrix}$$

and when this is substituted into () we obtain

$$(5) \quad \begin{aligned} \frac{\partial w_1}{\partial t} + u_0 \frac{\partial w_1}{\partial x} &= 0 & w_1 &= \rho - \frac{1}{c_0^2} p \\ \frac{\partial w_2}{\partial t} + (u_0 + c_0) \frac{\partial w_2}{\partial x} &= 0 & w_2 &= u + \frac{1}{\rho_0 c_0} p \\ \frac{\partial w_3}{\partial t} + (u_0 - c_0) \frac{\partial w_3}{\partial x} &= 0 & w_3 &= -u + \frac{1}{\rho_0 c_0} p \end{aligned}$$

Notice now how this breaks down into two separate cases. On the one hand, if flow is supersonic then all wave motion is in the left to right direction. In this case all analytic boundary conditions should be prescribed at the left hand side and only numerical boundary conditions prescribed at the right hand side.

Since the substitution (4) is equivalent to

$$\rho = K_1 + (\rho_0/2c_0)(K_2+K_3)$$

$$u = 1/2(K_2-K_3)$$

$$p = \rho_0 c_0 / 2 (K_2 + K_3)$$

it follows that prescribing all physical variables at the inflow and prescribing $\partial\rho/\partial x = \partial u/\partial x = \partial p/\partial x = 0$ at the outflow is legitimate in terms of analytical and numerical requirements in the supersonic case.

However, we must now consider the case of subsonic flow. In this case the situation is completely different. Here, two of the variables W_1 and W_2 go left to right with velocities u_0 and $u_0 + c_0$ respectively, whereas one of the variables runs right to left with velocity $c_0 - u_0$. The variables W_2 and W_3 have no clear physical significance, yet it is only in considering these variables that the full wave structure of the equations (5) or (6) can be understood. Thus, one would be led to predict, for small deviations from free stream conditions, that the best boundary conditions would be, for an interval $(0, L)$

$$\begin{aligned}
 (6) \quad w_1(0,t) &= K_1 & \frac{dw_1}{dx}(L,t) &= 0 \\
 w_2(0,t) &= K_2 & \frac{dw_2}{dx}(L,t) &= 0 \\
 \frac{dw_3}{dx}(0,t) &= 0 & w_3(L,t) &= K_3
 \end{aligned}$$

Note the curious aspect of these boundary conditions. In order to prescribe the numerical values K_1 and K_2 , we need to know accurately all three physical variables at some distance to the left. However, only the two combinations K_1 and K_2 are prescribed. This can be summarized by saying that while we have used all three pieces of information upstream, we have done so in such a way that one degree of freedom remains, thus allowing the waves in w_3 to exit without reflections.

On the basis of the linearized model, various other combinations would be well-posed. For example, it is possible to prescribe K_3 in terms of either K_1 or K_2 at the outflow $x = L$. Thus at the outflow one may prescribe

$$w_2(L,t) = F_3(t) + c_1 w_1(L,t) + c_2 w_2(L,t)$$

For example if $c_1 = 0$, $c_2 = 1$, then this amounts to putting

$$(7) \quad u(L,t) = 1/2 F_3$$

(i.e., we prescribe velocity at the outflow).

Alternatively, we might take $c_1 = 0$, $c_2 = -1$ and we would get

$$(8) \quad p(L,t) = ((\rho_0 c_0)/2)F_3$$

(i.e. we prescribe pressure at the outflow).

Many other combinations are possible, but as remarked in section II, all these will cause errors in the initial data to be reflected back into the medium as waves running from right to left. For example, we would predict that an error in W_3 would be reflected back as an error in W_1 if we use boundary condition (8). As we shall see, this is exactly what happens.

At the inflow end, we may prescribe W_1 and W_2 in terms of W_3 . Thus the following boundary conditions are well posed;

$$(9)(a) \quad W_1(0,t) = F_1 + c_1 W_3(0,t)$$

$$(b) \quad W_2(0,t) = F_2 + c_2 W_3(0,t)$$

For example, choosing $c_2 = +1$ in (9b) corresponds to

$$u(0,t) = (1/2)F_2$$

(i.e. prescribing u at the inflow) and $c_2 = -1$ corresponds to

$$p(0,t) = (\rho_0 c_0/2)F_2$$

(i.e. prescribing p). One can prescribe the combination (u, p) by first choosing $c_2 = 1$ (thereby prescribing u) and then choosing $c_1 = \rho_0/c_0$, thereby prescribing p in terms of a given F , and a

VI TWO DIMENSIONAL RESULTS

Having now understood the phenomena which can occur when calculations are made with one space dimension, we now consider the more complicated situation of two space dimensions.

In this situation, we shall solve the Navier Stokes equation (1), again by the standard MacCormack A.D.E. scheme on a 20 x 20 grid, which is a very simplified model of a wind tunnel. We shall continue to consider flow close to the free stream flow ($M_\infty = 0.5$) previously studied in the one dimensional case. The physical values are given earlier. Figure 8 shows the geometry of the situation. The fluid is flowing in at the top right corner of the grid and flowing out at the bottom left.

We have three distinct types of boundaries to consider. We have the inflow and outflow boundaries (as before) and in addition, two sidewall boundaries, where the fluid is flowing parallel to the boundary.

We shall continue to impose one dimensional boundary conditions of the type given in the first section on the inflow and outflow, along with the additional condition $v = 0$. This says the fluid flow is one dimensional at the inflow and outflow, and could be physically reasonable.

When we come to the sidewall conditions we must undertake another one-dimensional analysis. Thus, we assume all variables are constant in the x-direction and variation only takes place in the y-direction.

This leads to the set of equations

$$(6) \quad \dot{V}_t + AV_y = 0$$

where

$$\dot{\vec{V}} = \begin{bmatrix} p \\ u \\ v \\ e \end{bmatrix} \quad A = \begin{bmatrix} 0 & 0 & 1 & 0 \\ 0 & 0 & u & 0 \\ \frac{u^2}{2}(\gamma-1) & -u(\gamma-1) & 0 & \gamma-1 \\ 0 & 0 & \frac{e}{e}\gamma - \frac{u^2}{2}(\gamma-1) & 0 \end{bmatrix}$$

Freezing the coefficients of A in (6), we substitute

$$(7) \quad T_1 = \rho + \frac{p}{c_0^2}$$

$$T_2 = v + \frac{1}{\rho_0 c_0} p$$

$$T_3 = -v + \frac{1}{\rho_0 c_0} p$$

$$T_4 = u$$

Equation (6) is then transformed to

$$\begin{aligned}
 (8) \quad T_{1t} &= 0 \\
 T_{2t} + c_0 T_{2y} &= 0 \\
 T_{3t} - c_0 T_{3y} &= 0 \\
 T_{4t} &= 0
 \end{aligned}$$

Thus, if we only consider deviations transverse to the free stream flow, we have on the basis of the linearized model, four non-physical variable T_1, T_2, T_3, T_4 , two of which are u and entropy. T_1 move with zero velocity in the y direction, one of which, T_2 , moves with speed c_0 in the positive x direction, and one of which moves with speed c_0 in the negative x direction. Thus one dimensional theory predicts that at the sidewall, we should impose

$y = 0$	$y = L$
$T_{1y} = \text{const}$	$T_{1y} = 0$
$T_{3y} = 0$	$T_3 = \text{const}$
$T_{4y} = 0$	$T_{4y} = 0$

This, together with the inflow and outflow conditions gives the following set of boundary conditions

Inflow

$$v_1 = v_\infty$$

$$p_1 = \frac{1}{2} [p_2 + \rho_0 c_0 (k_3 - u_2)]$$

$$u_1 = \frac{1}{2} [k_3 - \frac{p_2}{\rho_0 c_0} + u_2]$$

$$\rho_1 = k_1 + \frac{\rho_0}{2c_0} [\frac{p_2}{\rho_0 c_0} + k_3 - u_2]$$

where the free stream values are specified in the characteristic variables $k_1 = \rho_\infty - p_\infty/c_0^2$, $k_3 = U_\infty + p_\infty/\rho_0 c_0$ and where the zero-subscript refers to frozen variables

Outflow

$$v_n = v_{n-1}$$

$$u_n = \frac{1}{2} [u_{n-1} + p_{n-1}/(\rho_0 c_0) - k_4]$$

$$p_n = \frac{\rho_0 c_0}{2} [k_4 + u_{n-1} + p_{n-1}/(\rho_0 c_0)]$$

$$\rho_n = \rho_{n-1} - \frac{p_{n-1}}{c_0^2} + \frac{\rho_0}{2c_0} [k_u + u_{n-1} + \frac{p_{n-1}}{\rho_0 c_0}]$$

Top wall

$$p_j = \frac{\rho_0 c_0}{2} \left[v_{j-1} + \frac{p_{j-1}}{\rho_0 c_0} - k_3 \right]$$

$$v_j = 1/2 k_3 + 1/2 (v_{j-1} + p_{j-1}/\rho_0 c_0)$$

$$\rho_j = \frac{\rho_0}{2c_0} \left(v_{j-1} + \frac{p_{j-1}}{\rho_0 c_0} - k_3 \right) + \rho_{j-1} - \frac{1}{c^2} p_{j-1}$$

$$u_j = u_\infty$$

Bottom wall

$$u_1 = u_\infty$$

$$v_1 = 1/2 [v_2 + k_2 - p_2/(\rho_0 c_0)]$$

$$p_1 = \frac{\rho_0 c_0}{2} [-v_2 + k_2 + p_2/(\rho_0 c_0)]$$

$$\rho_1 = \rho_2 + (\rho_0/2c_0) [-v_2 + k_2 - p_2/\rho_0 c_0]$$

where the free stream values are used to specify the characteristic combinations

$$w_2 = v_\infty + \frac{p_\infty}{\rho_0 c_0} \quad w_3 = v_\infty - p_\infty/\rho_0 c_0.$$

o

The purpose of the present grant was two-fold: first to expand the previous work to situations where the flow was at an angle α to the artificial boundary, but is primarily steady-state, and second, to see how the artificial boundary conditions apply in period situations where convergence to free stream is not expected.

The first objective is clearly desirable, simply to save in additional computing time. The requirement that the grid not be rectangular with boundaries either parallel to or perpendicular to the free stream at infinity clearly can be used to remove a large number of points from the grid. The entire boundary can be chosen approximately equidistant from the object whose flow characteristics are being studied.

The second objective was chosen because of its importance in modelling flow in the compressors of turbines. If one is attempting to design turbine compressors, one must have knowledge of how the flow in the area between the stators and the rotors is behaving. This is almost impossible to measure.

On the other hand, to accurately model the entire inside of the compressor requires a computational capability far exceeding the largest of today's computers. Thus one models only the flow past two blades of the rotor, and uses periodicity to extend the calculations to the entire rotor. The flow coming in past the

stator is regarded as a periodic inflow term.

The following pages summarize the results of the research on these two projects.

Section I Flow at an angle of incidence α .

The previously outlined boundary conditions were used. Computations were done on the basis of the inflow or outflow depending on the flow perpendicular to the surface. For computational simplicity, we chose a rectangular grid, but choose $u_{\infty} = v_{\infty} = 300$. This results in a 45° angle of incidence or exit. We impose an initial 10% disturbance in W_2 , the right running characteristic variable and observe what happens as it exits. Recall that this disturbance runs at an angle of 45° to the flow. The following plots for W_2 at various iteration numbers show it exiting without any surprising phenomena, similar to the one-dimensional case. By the sixty-fifth iteration, the flow has almost converged to steady state. There appear to be some small reflections (as shown in the last plot) in W_3 , but nothing to worry about.

Thus we can conclude that the inflow-outflow boundary conditions work reasonably well. Subject to a rotation of coordinates, they can work on any geometry - the only decision is whether we are at an inflow or outflow point.

II. The case of periodic BCs

We now consider some experiments on the case of periodic boundary conditions. We study flow parallel to the rectangular grid, perpendicular to the inflow and parallel to the side-walls.


The most obvious boundary condition is pure periodic. $S_1 = S_{n-1}$, $S_n = S_2$ for all physical variables S . This, it was feared might lead to over specification, but these fear appeared groundless. A sight-traveling wave would exit to the right, and reappear at the left in a predictable and correct manner.

The next objective was to see if this could be done by only using periodicity in the two sideways traveling periodic waves. The reason for this was to minimize storage problems for the more complicated turbine problem already discussed.


Curiously, this method failed. Furthermore, the failure seems intrinsic to the whole idea, as we shall demonstrate.

First the W_2 wave appears in iteration 5 and proceeds to exit. Periodicity requires that it reappear, and this can be seen in iteration 20. However, already, a sharp spike (reminiscent of over specification is appearing in W_3 by iteration 20. As far as iteration 40 W_2 continues to progress from right to left, but at iteration 55, sharp spikes begin to develop in W_2 and W_3 . This seems to suggest overspecification at the corners, but as far as we know, this is not the problem. Shortly afterwards the program crashes. The relevant portion of the program for the boundary condition implementation is included.


ITERATION NUMBER = 5




ITERATION NUMBER = 10




ITERATION NUMBER = 15




ITERATION NUMBER = 20




ITERATION NUMBER = 25




ITERATION NUMBER = 30




ITERATION NUMBER = 35




ITERATION NUMBER = 40




ITERATION NUMBER = 45



ITERATION NUMBER = 60




ITERATION NUMBER = 65





```

000501  RHOP(1,1,1)/RHOP(K,2,1)*(PP(K,1)-PP(K,2))/(CINF**2)
000502  PHOE(1,1,1)*(PP(K,1)*CU)/(RHOU(K,1,1)**2)*(RHOU(K,1,1)*
000503  1/2)*(RHOP(1,1,1)*2.0)
000504  CONTINUE
000505  2
000506  UPSTREAM & DOUNSTREAM BOUNDARY CONDITIONS
000507  ***** UPSTREAM *****
000508  DO 3 J=1, JL
000509  1--RHOP(1,J,1)=AK1*(RHOU(K,2,1)*CINF)**2*((PP(2,J)/(RHOU(K,2,1)*AK3
000510  1--RHOU(2,J,1)/RHOP(2,J,1)))
000511  RHOU(1,J,1)=RHOP(1,J,1)*0.5*(AK3-(PP(2,J)/(RHOU(K,2,1)*AK3
000512  1--RHOU(2,J,1)/RHOP(2,J,1)))
000513  RHOP(1,J,1)=RHOU(2,J,1)
000514  PP(1,J)=0.5*(PP(2,J)+RHOU(K,2,1)*CINF*(AK3-(RHOU(2,J,1)/RHOP(2,J,1)))
000515  PHOE(1,J,1)=PP(1,J)*CU/(RHOU(1,J,1)**2)*(RHOU(1,J,1)*
000516  1--RHOP(1,J,1)*2.0)
000517  ***** DOUNSTREAM *****
000518  RHOP(1,J,1)=RHOP(KLM,J,1)-PP(KLM,J)/(CINF**2)*(RHOU(K,2,1)*CINF)**2)
000519  1--AK4*(RHOU(KLM,J,1)/RHOP(KLM,J,1)+(PP(KLM,J)/(RHOU(K,2,1)*CINF)**2)
000520  RHOU(KLM,J,1)=0.5*(RHOP(KLM,J,1)
000521  RHOP(KLM,J,1)=0.5*(RHOP(KLM,J,1)+RHOU(KLM,J,1)/RHOP(KLM,J,1)-AK4
000522  1--PP(KLM,J)/(RHOU(K,2,1)*CINF)**2)
000523  PP(KLM,J)=0.5*(PP(KLM,J)+RHOU(K,2,1)*CINF*(AK4-(RHOU(KLM,J,1)/RHOP(KLM,
000524  1--RHOP(KLM,J,1)))
000525  RHOU(KLM,J,1)=PP(KLM,J)*CU/(RHOU(KLM,J,1)**2)*(RHOU(KLM,J,1)*
000526  1--RHOP(KLM,J,1)*2.0)
000527  CONTINUE
000528  3
000529  GO TO 100
000530  ***** CORRECTOR SLEEP *****
000531  *****
000532  10 CONTINUE
000533  DO 16 J=1, JL
000534  DO 16 K=1, KL
000535  P(K,J)=(RC/CU)*(RHOE(K,J,1)-((RHOU(K,J,1)**2)*(RHOU(K,J,1)**2)/
000536  1--2.0*(RHOU(K,J,1)))
000537  16 CONTINUE
000538  DO 26 K=1, KL
000539  U31(K)=P(K,2)/(RHOU(K,2,1)*CINF)-RHOU(K,2,1)/RHO(K,2,1)
000540  U2J(L)=P(K,JL)/(RHOU(K,1)*CINF)+RHOU(K,JL,1)/RHO(K,JL,1)
000541  CONTINUE
000542  26
000543  TRANSVERSE BOUNDARY CONDITIONS
000544  ***** TOP FAR FIELD *****
000545  DO 11 K=1, KL
000546  RHOU(K,JL,1)=RHOU(K,JL,1)
000547  RHOU(K,JL,1)=0.5*(RHOU(K,JL,1)*((U31(K)-RHOU(K,JL,1)/RHO(K,JL,1)
000548  1--P(K,JL)/(RHOU(K,1)*CINF)**2)
000549  P(K,JL)=0.5*(RHOU(K,JL,1)*CINF*(U31(K)+RHOU(K,JL,1)/RHO(K,JL,1)+
000550  1--P(K,JL)/(RHOU(K,1)*CINF)**2)
000551  11
000552  12
000553  13
000554  14
000555  15
000556  16
000557  17
000558  18
000559  19
000560  20
000561  21
000562  22
000563  23
000564  24
000565  25
000566  26
000567  27
000568  28
000569  29
000570  30
000571  31
000572  32
000573  33
000574  34
000575  35
000576  36
000577  37
000578  38
000579  39
000580  40
000581  41
000582  42
000583  43
000584  44
000585  45
000586  46
000587  47
000588  48
000589  49
000590  50
000591  51
000592  52
000593  53
000594  54
000595  55
000596  56
000597  57
000598  58
000599  59
000600  60
000601  61
000602  62
000603  63
000604  64
000605  65
000606  66
000607  67
000608  68
000609  69
000610  70
000611  71
000612  72
000613  73
000614  74
000615  75
000616  76
000617  77
000618  78
000619  79
000620  80
000621  81
000622  82
000623  83
000624  84
000625  85
000626  86
000627  87
000628  88
000629  89
000630  90
000631  91
000632  92
000633  93
000634  94
000635  95
000636  96
000637  97
000638  98
000639  99
000640  100
000641  101
000642  102
000643  103
000644  104
000645  105
000646  106
000647  107
000648  108
000649  109
000650  110
000651  111
000652  112
000653  113
000654  114
000655  115
000656  116
000657  117
000658  118
000659  119
000660  120
000661  121
000662  122
000663  123
000664  124
000665  125
000666  126
000667  127
000668  128
000669  129
000670  130
000671  131
000672  132
000673  133
000674  134
000675  135
000676  136
000677  137
000678  138
000679  139
000680  140
000681  141
000682  142
000683  143
000684  144
000685  145
000686  146
000687  147
000688  148
000689  149
000690  150
000691  151
000692  152
000693  153
000694  154
000695  155
000696  156
000697  157
000698  158
000699  159
000700  160
000701  161
000702  162
000703  163
000704  164
000705  165
000706  166
000707  167
000708  168
000709  169
000710  170
000711  171
000712  172
000713  173
000714  174
000715  175
000716  176
000717  177
000718  178
000719  179
000720  180
000721  181
000722  182
000723  183
000724  184
000725  185
000726  186
000727  187
000728  188
000729  189
000730  190
000731  191
000732  192
000733  193
000734  194
000735  195
000736  196
000737  197
000738  198
000739  199
000740  200
000741  201
000742  202
000743  203
000744  204
000745  205
000746  206
000747  207
000748  208
000749  209
000750  210
000751  211
000752  212
000753  213
000754  214
000755  215
000756  216
000757  217
000758  218
000759  219
000760  220
000761  221
000762  222
000763  223
000764  224
000765  225
000766  226
000767  227
000768  228
000769  229
000770  230
000771  231
000772  232
000773  233
000774  234
000775  235
000776  236
000777  237
000778  238
000779  239
000780  240
000781  241
000782  242
000783  243
000784  244
000785  245
000786  246
000787  247
```



ITERATION NUMBER = 1



ITERATION NUMBER = 5




ITERATION NUMBER = 10




PL


ITERATION NUMBER = 15




ITERATION NUMBER = 20




ITERATION NUMBER = 20




ITERATION NUMBER = 25




ITERATION NUMBER = 25




ITERATION NUMBER = 30




ITERATION NUMBER = 35




ITERATION NUMBER = 40




ITERATION NUMBER = 40




ITERATION NUMBER = 55




ITERATION NUMBER = 55



ITERATION NUMBER = 65






Finally, we attempted to run periodic characteristic B.C.s on a one-dimensional basis. We felt that since the problem manifested itself at the corners, if we removed the corners the problem should go away. We next show what happened in this situation.


First we see the one-dimensional wave in W_2 moving to the right, exiting and reappearing by the iteration 20. However, sharp spikes appear in W_3 by this time. W_2 appears to behave well until iteration 85, but either reflection or some non-linear instability lies caused W_3 to grow catastrophically. Clearly this represents failure of the boundary conditions, even in the one-dimensional case.

Various minor variations were tried, but all produced the same basic phenomena.

[142] 10 sten

PURNEY






20.45


W13


20 in



W2

85 ton





N3

85 mten

Conclusion

Non-reflecting characteristic boundary conditions work well so long as the flow is basically returning to steady state. This was seen in the first series of numerical experiments.

However, at this stage of development they cause strange instabilities which prevent efficient modelling of periodic phenomena. The reasons for this are not understood at the present.

BIBLIOGRAPHY

- [1] Engquist, B., and Majda, A., "Absorbing Boundary Conditions for the Numerical Simulation of Waves", Math Comp. Vol. 31, pp 629-651, (1977).
- [2] Gottlieb, D., and Turkel, E., "Boundary Conditions for Multi-Step Finite Difference Methods for Time Dependent Equations", J. Comp. Phys. Vol. 26, pp 181-196 (1978).
- [3] Gustaffson, B., and Kriess, H.O., "Boundary Conditions for Time Dependent Problems with an Artificial Boundary", Jour. Comp. Phys. Vol. 30, pp 333-351 (1979).
- [4] Gustaffson, B., Kreiss, H.O., and Sundstrom, A., "Stability Theory of Difference Approximations for Mixed Initial Boundary Value Problems II", Math. Comp., Vol. 26, pp 649-686 (1972).
- [5] Kreiss, H.O., "Stability Theory for Difference Approximations of Mixed Initial Boundary Value Problems I", Math. Comp., Vol. 22, pp 703-714 (1968).
- [6] MacCormack, R.W., "Numerical Solutions of the Interactions of a Shock Wave with Laminar Boundary Layer", Lecture Notes in Physics, Vol. 19, Springer Verlag (1976).
- [7] McKenna P.J., Graham, J.E., and Hankey, W.L., The role of far-field boundary conditions in numerical solutions of the Navier-Stokes equations, AFWAL Tech. Report TR. 81.
- [8] Moretti, G., Comment on "Stability Aspects of Divergent Subsonic Flow", AIAA Jour., Vol. 19, No. 5., p 669 (1981).
- [9] Oliger, J., and Sundstrom, A., Theoretical and practical aspects of some initial boundary value problems in fluid dynamics, SIAM J. of Appld. Math., 35 (1978) pp. 419-446.
- [10] Parter, S.V., "Stability, Convergence and Pseudo-Stability of Finite Difference Equations for an Over-Determined Problems", Numer. Math., Vol. 4, pp 277-292 (1962).
- [11] Rudy, D.H., and Strikwerda, J.S., "Boundary Conditions for Subsonic Compressible Navier-Stokes Equations", Computers and Fluids, Vol. 9, pp 327-338 (1981).
- [12] Rudy, D.H., and Strikwerda, J.C., "A Non-reflecting Outflow Boundary Condition for Subsonic Navier-Stokes Calculations", Jour. Compu. Phys. Vol. 36, pp 55-70 (1980).

- [13] Schlichting, H., "Boundary Layer Theory". Seventh Edition, McGraw Hill N.Y. (1979).
- [14] Shang, J.S., Oscillatory compressible flow round a cylinder, Proc. AIAA 20th Aerospace Meeting, Jan 11-14 (1982). Orlando, Florida.
- [15] Shang, J.S., "Numerical Simulation of Wing Fuselage Interference", AIAA 19th Aerospace Sciences Meeting, AIAA-81-0048, Jan 12-15, 1981.
- [16] Steger, J.L., Pulliam, T.H., and Chima, R.V., "An Implicit Finite Difference Code for Inviscid and Viscous Cascade Flow", AIAA Preprint-80-1427, AIAA 13th Fluid and Plasma Dynamics Conference, July 14-16, 1980.
- [17] Yee, H.C., "Numerical Approximation of Boundary Conditions with Application to Inviscid Equation of Gas Dynamics", NASA Technical Memorandum 81265, March 1981.
- [18] Yee, H.C., R.M., Beam, and Warming, R.F., "Stable Boundary Approximations for a Class of Implicit Schemes for the One-Dimensional Inviscid Equation of Gas Dynamics", AIAA Paper 81-1009, presented at Palo Alto, CA, June 1981.

END

FILMED

10-85

DTIC